



**Professional
Ironing
Systems**



AQUASTAR
LAUNDRY SOLUTIONS

P-M Series

FLATWORK IRONERS



This range of Flatwork Ironers is specially designed for the restaurant and low production, and is ideal for ironing flatwork-tablecloths, sheets, napkins, pillowcases, etc.

- Front insertion and reception of linen
- External cabinet in Skin-plate.
- Uniform chest pressure throughout years of operation.
- Safety-Sensor.
- Electronic microprocessor for temperature control.
- Emergency stop button.
- Roller covered in polyester with cotton sheath or NOMEX

RELIABLE AND DURABLE

Only ELECTRIC HEATING version.

The linen should be passed through the dryer before hand to reach the moisture level of 20-25% for the optimum quality ironing.

Their simple mechanism makes them reliable and durable, meaning that this is the most economical and safe option for a small laundry.

FOR SMALLER SPACES

Wall mounted and small in size, they can be positioned in very limited spaces and require hardly any installation since they do not have any kind of exhaust or connection, except to the electricity supply.

P-M Series

| Model | Ø Cylinder | Usable Length | Hourly Production | Electric Heating | Dimensions L x P x H mm | Net Weight |
|----------|------------|---------------|-------------------|------------------|-------------------------|------------|
| P 1018 M | Ø 180 | mm. 1000 | Kg/h. 15 ÷ 20 | Kw. 3,32 | 1370 x 400 x 952 | Kg. 80 |
| P 1218 M | Ø 180 | mm. 1200 | Kg/h. 20 ÷ 25 | Kw. 4,03 | 1570 x 400 x 952 | Kg. 90 |
| P 1025 M | Ø 250 | mm. 1000 | Kg/h. 30 ÷ 35 | Kw. 5,13 | 1462 x 484 x 985 | Kg. 114 |
| P 1225 M | Ø 250 | mm. 1200 | Kg/h. 35 ÷ 40 | Kw. 6,18 | 1662 x 484 x 985 | Kg. 124 |
| P 1425 M | Ø 250 | mm. 1400 | Kg/h. 40 ÷ 45 | Kw. 7,18 | 1862 x 484 x 985 | Kg. 134 |
| P 2025 M | Ø 250 | mm. 2000 | Kg/h. 50 ÷ 65 | Kw. 12,18 | 2462 x 484 x 985 | Kg. 164 |

I 32 M Series

FLATWORK DRYERS IRONERS WITH CYLINDER OF Ø 325



Our range of flatwork ironers **I 32 M** represents a new concept in improving and speeding up the flatwork drying and ironing process in the industrial laundry area. Our complete offer has been totally renewed and redesigned to cater for the increasingly tougher demands of the laundry and hospitality industry.

The main feature of these machines is that the linen can be fed directly to the flatwork ironer from the high spin washer extractor. They permit a moisture level of up to 45-50% and all in all they provide high-quality ironing, great ergonomics and top performance, combined with easy maintenance and use.

The flatwork dryer ironers **I 32 M** series is fitted with a roll covered in **NOMEX** which permits to easily iron any kind of flat linen (such as tablecloths, napkins, sheets, a.s.o.). The loading and unloading of laundry is front thus allowing also a mural installation.

I 32 M series is available with **ELECTRIC** or **GAS** heating system.

The use is particularly recommended for medium size laundries processing also high volumes.

Using a roller with Ø 325 mm in diameter you can obtain a rapid ironing and an optimal drying.

- Outer cabinet in stainless steel.
- Cylinder diameter of Ø 325 mm.
- ELECTRIC or GAS Heating.
- Feeling and ironing belts in NOMEX.
- Polished steel cylinder.
- Electronic Microprocessor for temperature and speed control.
- Automatic control.
- Frequency inverter.
- Steam extractor.
- Can be leaned against the wall.
- Finger guard protection.
- Frontal Inlet and outlet of the linen.

I 32 M Series

| Model | Ø Cylinder | Usable Length | Hourly Production | Dimensions L x P x H mm | Net Weight |
|----------|------------|---------------|-------------------|-------------------------|------------|
| I 1432 M | Ø 325 | mm. 1400 | Kg/h. 10 ÷ 20 | 1960 x 644 x 1107 | Kg. 300 |
| I 1632 M | Ø 325 | mm. 1600 | Kg/h. 20 ÷ 30 | 2210 x 644 x 1107 | Kg. 355 |
| I 2032 M | Ø 325 | mm. 2000 | Kg/h. 30 ÷ 40 | 2560 x 644 x 1107 | Kg. 405 |

I 50 TC2 Series

FLATWORK DRYERS IRONERS WITH CYLINDER OF Ø 500



Our range of flatwork ironers **I 50 TC2** represents a new concept in improving and speeding up the flatwork drying and ironing process in the industrial laundry area. Our complete offer has been totally renewed and redesigned to cater for the increasingly tougher demands of the laundry and hospitality industry.

The main feature of these machines is that the linen can be fed directly to the flatwork ironer from the high spin washer extractor. They permit a moisture level of up to 45-50% and all in all they provide high-quality ironing, great ergonomics and top performance, combined with easy maintenance and use.

The flatwork dryer ironers **I 50 TC2** series is fitted with a roll covered in **NOMEX** which permits to easily iron any kind of flat linen (such as tablecloths, napkins, sheets, a.s.o.). The loading and unloading of laundry is front thus allowing also a mural installation.

I 50 TC2 series is available with **ELECTRIC, STEAM** or **GAS** heating system.

The use is particularly recommended for medium size laundries processing also high volumes.

Using a roller with Ø 500 mm in diameter you can obtain a rapid ironing and an optimal drying.

- Cylinder diameter of Ø 500 mm.
- ELECTRIC, STEAM or GAS Heating.
- Feeling and ironing belts in NOMEX.
- Polished steel cylinder.
- Touch Screen Computer with 7" colour display.
- Automatic control.
- Frequency inverter.
- Steam extractor.
- Can be leaned against the wall.
- Finger guard protection.
- Frontal Inlet and outlet of the linen.
- Inversion of standard roller



Touch Screen Computer with 7" colour display

I 50 TC2 Series

| Model | Ø Cylinder | Usable Length | Hourly Production | Dimensions L x P x H mm | Net Weight |
|------------|------------|---------------|-------------------|-------------------------|------------|
| I 2050 TC2 | Ø 500 | mm. 2000 | Kg/h. 50 ÷ 70 | 2820 x 1070 x 1420 | Kg. 930 |
| I 2650 TC2 | Ø 500 | mm. 2600 | Kg/h. 60 ÷ 80 | 3445 x 1070 x 1420 | Kg. 1180 |
| I 3350 TC2 | Ø 500 | mm. 3300 | Kg/h. 80 ÷ 120 | 4145 x 1070 x 1420 | Kg. 1430 |

I 65 TC2 Series

FLATWORK DRYERS IRONERS WITH CYLINDER OF Ø 650



Our range of flatwork ironers **I 65 TC2** represents a new concept in improving and speeding up the flatwork drying and ironing process in the industrial laundry area. Our complete offer has been totally renewed and redesigned to cater for the increasingly tougher demands of the laundry and hospitality industry.

The main feature of these machines is that the linen can be fed directly to the flatwork ironer from the high spin washer extractor. They permit a moisture level of up to 45-50% and all in all they provide high-quality ironing, great ergonomics and top performance, combined with easy maintenance and use.

The flatwork dryer ironers **I 65 TC2** series is fitted with a roll covered in **NOMEX** which permits to easily iron any kind of flat linen (such as tablecloths, napkins, sheets, a.s.o.). The loading and unloading of laundry is front thus allowing also a mural installation.

I 65 TC2 series is available with **ELECTRIC, STEAM** or **GAS** heating system.

The use is particularly recommended for medium size laundries processing also high volumes.

Using a roller with Ø 650 mm of diameter you can obtain a rapid ironing and an optimal drying.

- Cylinder diameter of Ø 650 mm.
- ELECTRIC, STEAM or GAS Heating.
- Feeling and ironing belts in NOMEX.
- Polished steel cylinder.
- Touch Screen Computer with 7" colour display.
- Automatic control.
- Frequency inverter.
- Steam extractor.
- Can be leaned against the wall.
- Finger guard protection.
- Frontal Inlet and outlet of the linen.
- Inversion of standard roller



Touch Screen Computer with 7" colour display

I 65 TC2 Series

| Model | Ø Cylinder | Usable Length | Hourly Production | Dimensions L x P x H mm | Net Weight |
|------------|------------|---------------|-------------------|-------------------------|------------|
| I 2065 TC2 | Ø 650 | mm. 2000 | Kg/h. 65 ÷ 90 | 2845 x 1070 x 1420 | Kg. 1189 |
| I 2665 TC2 | Ø 650 | mm. 2600 | Kg/h. 80 ÷ 105 | 3445 x 1070 x 1420 | Kg. 1517 |
| I 3365 TC2 | Ø 650 | mm. 3300 | Kg/h. 105 ÷ 160 | 4145 x 1070 x 1420 | Kg. 1765 |



AQUASTAR
LAUNDRY SOLUTIONS

Via Verde 7/D
40012 Calderara di
Reno Bologna - Italy
tel. +39 051 722587
fax +39 051 723967

www.aquastar.it

